

Data Sheet

Reference No.: 40001

Transfer Press -mechanical-

Brand: PLATARG
Model: 611
YoM, approx.: overhauled
Reconditioned: 2025
Controls: PLC SCHNEIDER



Press Design

drive system: eccentric / crank
number of slide actions: 11
feedstock transport direction: left to right

Press forces

total force (nominal): 66 to

Slide

slide force: 6 to
stroke: 114 mm

slide (mechan. Press)

variable speed: yes
stroke rate (min.): 40 /min
stroke rate (max.): 130 /min
main drive power: 7.5 kW

Strip-Feeder

feeder type: roll feeder

Transfer System

distance between tools, stroke X fixed: 82 mm

Dimensions / weights

space requirements -left/right-: 2875 mm
space requirements -front/back-: 1500 mm
total height: 2900 mm
total weight approx.: 7500 kg

Attachments (presses)

safety guard / safety door: yes
2-hand engagement: yes
noise protection cabin: yes
acc. to actual accident protection regulation: yes

Additional Information:

Specifications:
Number of stations: 12 (11+1)
Capacity per ram: 6 tons
Maximum stroke: 114 mm
Max. shell height: 50 mm
Standard ram pitch: 82 mm
Blank diameter: 80 mm
Maximum speed: 80 spm

Example of an overhauled machine which can be applied to a machine of the same model which is currently available in our database and includes the supply of this machine. Most specifications can be modified / upgraded according to customer's requirements. Please supply us with your complete specifications in order to make a detailed offer

Seller:


Post-Venta Carreras S.A.
Sean Gribben
Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
La Pobla de Claramunt, Spain
+34 938 088 099
sean@prodeq.es

Photos & Documents

Reference No.: 40001



LHS



Cams



Full



Without Cabin